

VaporBoot G Installation Instructions

Part Number: VBOOTGOS • Package Contents: 25 Each VaporBoot-G 18" x 18" & 1 Roll VaporBoot Tape 2" x 16.4'



Trace or measure the pipe size onto VaporBoot G material. Cut a hole approximately 1/2" smaller than outside diameter of pipe. Make several 1/4" long cuts from inside of hole in four to eight places depending upon size of pipe. This will allow pipe to fit tightly in the hole and VaporBoot G to stretch around the pipe.



Force VaporBoot G over pipe leaving the tightly stretched cut area taut around bottom of pipe with approximately a 1/2" of the VaporBoot G material running vertically up the pipe. (No more than a 1/2" of stretched material is recommended to allow tape to adhere directly to pipe.)



Take VaporBoot tape (supplied in VaporBoot G System package) and cut to length by measuring around pipe allowing approximately 1" extra for overlap sealing. Fold VaporBoot tape in half lengthwise forming a crease.



Peel off only one of the two paper release liners and apply tacky side of folded tape to the base of pipe penetration, keeping tape folded in lengthwise position. Once tape has been wrapped completely around pipe, carefully overlap ends at least 1/2" to 1" by tucking end into starting position to make a continuous seal (the very end of outside release liner will need to be peeled back about 1 1/2" to make this overlap).



Leaving VaporBoot tape in folded position, remove entire outside release liner. Place fingers on inside of folded tape and slowly start working tape outward avoiding any folds or wrinkles in tape. Once VaporBoot tape is completely applied, press around entire section to verify seal.



Finish VaporBoot G installation by taping exterior edge of the boot down onto VaporBlock[®]G™ vapor retarder with Raven VaporBond seaming tape (sold separately) or an approved equal.